

**TOOLS & EQUIPMENT REQUIRED SPECIFICATION LIST**  
**SUBJECT AREA : FURNITURE PRODUCTION AND WOOD WORKING**

NO.	NAME AND SPECIFICATION OF TOOLS AND EQUIPMENT	TOTAL QTY
1	<p><b>Geometry Set</b></p> <p><b>Feature :</b>            * Durable, professional grade instruments            * Made of transparent yellow plastic            * Tracing edge and millimetre scale</p> <p><b>Specification :</b>            Flat ruler 300 mm : 1 pc            Set square 45°, 200 mm : 1 pc            Set square 30° / 60° triangles 20 mm : 1 pc            Semi-circular protactor : 1 pc            All compartments inside a high impact plastic case</p>	96 Set
2	<p><b>Compasses</b></p> <p><b>Feature :</b>            * Instrument have a durable matte nickel finish over hardened brass            * All instruments and parts rest in cushioned foam tray compartments inside a high impact plastic case</p> <p><b>Specification :</b>            Versatile set contains large and small bow combinations 155mm. Friction head dividers, 150mm beam bar extension, pen handle, screwdriver, and vial with leads and needle part small pen included.            Shank dia. = 3.5 mm</p>	48 Set
3	<p><b>Universal Stainless Steel Protactor</b></p> <p>Halfround head 0 - 180°            made of stainless steel, good quality            Dimension : 90 x 150 mm</p>	24 Pcs
4	<p><b>Ellipse Templates</b></p> <p><b>Feature :</b>            Combination ellips master projection of 20°, 25°, 30°, 35°, 40°, 45°, 50°, and 60°. Made of transparance fiber glass / acrylic.</p> <p><b>Size ring :</b>            20° - 4 to 40mm            25° - 4 to 40mm            30° - 4 to 38mm            35° - 4 to 38mm            40° - 4 to 35mm</p>	48 Pcs

NO.	NAME AND SPECIFICATION OF TOOLS AND EQUIPMENT	TOTAL QTY
5	<p>45° - 4 to 38mm            50° - 4 to 30mm            60° - 4 to 30mm  <b>Specification :</b>            Size : 265 x 145 x 1.2mm</p> <p><b>Circle Templates</b></p> <p><b>Feature :</b>            Made of transparance fiber glass/acrylic            36 circles ranging in diameter, with millimeter ruler and fingerlift.            Size from 1mm through 36mm in 1mm increment.</p> <p><b>Specification :</b>            Dimension : 129 x 255 x 1.2mm</p>	48 Set
6	<p><b>Adjustable French Curves</b></p> <p><b>Feature :</b>            Easily shaped into any smooth curve. Anger shaped and held in position by friction. Length approx. 450mm            Made of Elastic Hard Rubber</p>	48 Set
7	<p><b>T-square</b></p> <p><b>Specification :</b>            Aluminum            Size = 24"</p>	96 Pcs
8	<p><b>Lettering Guide</b></p> <p><b>Feature :</b>            Letters A through Z and numbers 0 through 9 in three size on template.</p> <p><b>Specification :</b>            Character Height = 2 mm            Character Height = 3 mm            Character Height = 5 mm            Made of Transparance Fibber Glass / Acrylic</p>	48 Pcs
9	<p><b>Tape Rules</b></p> <p><b>Feature :</b>            Tempered spring steel blade with bold black and red markings.            Coated with abrasive resistant material.            Chrome plate case.            Furnished with removable belt clip</p> <p><b>Specification :</b>            Length of blade = 3.5 m            Width of blade = 16 mm</p>	48 Pcs

NO.	NAME AND SPECIFICATION OF TOOLS AND EQUIPMENT	TOTAL QTY
10	<p><b>Folding Rule</b></p> <p><b>Feature :</b>  Made of fiberglass-Flexible yet durable. Marked both sides and edges.  English metric-English graduation : outside market consecutive inches to 16 tks. Inside face consecutive centimeters to millimeters.  Each 10th centimeter marked in red</p> <p><b>Specification :</b>  Metric, English - graduations  Length = 1 m  Width = 17 mm  Reading type = outside</p>	24 Pcs
11	<p><b>Vernier Caliper</b></p> <p><b>Feature :</b>  Hardened stainless steel, ground and lapped.Satin chrome finish with engraved micro-fine graduation. Has jaw designed for outside, inside, depth and depth measurement.</p> <p><b>Specification :</b>  Inch - metric graduations  Range : 0 - 6"  Vernier scale = 1/16", 1/32"  Vernier scale = 1/128"</p>	8 Pcs
12	<p><b>Outside Caliper</b></p> <p><b>Feature :</b>  Yankee spring caliper with flat stock legs.</p> <p><b>Specification :</b>  Size : 3"</p>	8 Pcs
13	<p><b>Inside Caliper</b></p> <p><b>Feature :</b>  Yankee spring caliper with flat stock legs.  Made of fully polished forged steel</p> <p><b>Specification :</b>  Size : 6"</p>	8 Pcs
14	<p><b>Wing Divider (Spring Dividers)</b></p> <p><b>Feature :</b>  For transferring or scribing arcs and circles in lay out work.  Made of fully polished forged steel. Hardened points precision screw threads.</p>	8 Pcs

NO.	NAME AND SPECIFICATION OF TOOLS AND EQUIPMENT	TOTAL QTY
	Carefully tempered spring for easy adjustment while holding legs firmly in place.	
15	<p><b>Specification :</b> Size : 6"</p> <p><b>Try and Meter Square</b></p> <p><b>Feature :</b> Designed for making 90° and 45° angles for picture framing or installing molding. Steel blade edges, machined parallel, are square inside and out. Number and 1/8" graduations.</p> <p><b>Specification :</b> Metric graduation Length of blade : 8" Length of handle : 5"</p>	24 Pcs
16	<p><b>Combination Square</b></p> <p><b>Feature :</b> Use as a rule, try &amp; meter square, depth or marking gauge 90° &amp; 45° level, removable steel blades, graduated on both sides, top and bottom edges.</p> <p><b>Specification :</b> Metric graduation Length of blade : 12"</p>	8 Pcs
17	<p><b>Sliding T-Bevel</b></p> <p><b>Specification :</b> Hard wood handle with brass tips and locking device - Black finish. Sliding 5" T - bevel adjusts to any angle Length of blade : 8"</p>	8 Pcs
18	<p><b>Marking Gauge</b></p> <p><b>Feature :</b> Made of selected hardwood, vanished finish and fitted with brass Thumbscrew. Hardened steel spur.</p> <p><b>Specification :</b> Length both : 164.5mm</p>	48 Pcs
19	<p><b>General Purpose Hardpoint Handsaw</b></p> <p><b>Feature :</b></p>	24 Pcs

NO.	NAME AND SPECIFICATION OF TOOLS AND EQUIPMENT	TOTAL QTY
20	<p>Blad in cold-rolled stainless strip steel, teeth arranged in single cutting direction, precision-crossed and cross-ground, tooth tips electroinduction hardened, high-quality closed hardwood handle. The tough plastic handle is fixed to the blade by three sawscrews and incorporates at 45° and 90° angle feature.</p> <p><b>Specification :</b> Length of Blade = 500 mm Point per Inch = 8</p> <p><b>Cross Cut Saw</b></p>	96 Pcs
21	<p><b>Feature :</b> The ground tooth design (super cut) gives the saw excellent cutting capacity superior to conventional universal tothing. The extra hardened tooth points make the saw stay sharp 3-5 times longer than conventional saws.</p> <p><b>Specification :</b> Length : approx 600 mm Pts/inch : 8</p> <p><b>Rip - Saw</b></p>	96 Pcs
22	<p><b>Feature :</b> From high alloy steel. Filled and set teeth inclined teeth - for rip sawing. The teeth at the pointed end are chamfer filed to avoid jumping. Plastic handle.</p> <p><b>Specification :</b> Length : approx 600 mm Pts/inch = 8</p> <p><b>Compass Saw</b></p>	8 Pcs
23	<p><b>Feature :</b> Heavy duty for rough cutting through wood, plastic and fiberboard. Ideal for cutting rained holes for pipe and tubing. Alloy steel blade is held by stud and wing nut.</p> <p><b>Specification :</b> Length = approx 300 mm Pts/inch = 8</p> <p><b>Key Hole Saw</b></p>	8 Pcs
24	<p><b>Feature :</b> Blade rotate and locks in any one of eight different positions. Quick acting chuck hold blades firmly in die cast handle. For use on Wood, Metal, Drywall</p> <p><b>Specification :</b> Furnished with three interchangeable blades.</p> <p><b>Coping Saw</b></p>	8 Pcs

NO.	NAME AND SPECIFICATION OF TOOLS AND EQUIPMENT	TOTAL QTY
25	<p><b>Feature :</b> Spring steel rounded edge frame with straight plastic handle. Adjustable angle blade.</p> <p><b>Specification :</b> Length of blade = approx 160 mm Depth length frame = approx 110 mm Overall length = 12½" Supplied completed with 1 Doz of blades. With size of blade has approx 15 points per inches</p>	24 Pcs
26	<p><b>Feature :</b> For cutting many shape of sheet wood Hardwood handle</p> <p><b>Specification :</b> Depth of frame approx, 300 mm Completed with 12 pcs spare blade with 3 different size of teeth, for wood, plastic, and metal</p>	24 Pcs
27	<p><b>Feature :</b> Alloy steel blades, comfort grip wood handles and milled, set, bevel filed teeth.</p> <p><b>Specification :</b> Pts/in = 12 Size = 12" x 3"</p>	16 Unit
28	<p><b>Feature :</b> For miter cutting/many angle of cutting body made of cast iron, finely part of guider, complete with scale angle and locking screw. - Length of saw approx. : 550 mm - width of saw approx. : 45 mm - Height of cut approx. : 100 mm - width of cut approx. : 120 mm - Angle capacity approx. : 45 up to 90°, left and right supplied complete with "back saw"</p> <p><b>Feature :</b> Alloy steel blades, comfort grip wood / plastic / metal handle. Used cut small wood, from variety of angles</p> <p><b>Specification:</b> Miter Saw approx. : 500 mm Based mitre saw made of best quality hard wood</p>	8 Unit

NO.	NAME AND SPECIFICATION OF TOOLS AND EQUIPMENT	TOTAL QTY
29	<p><b>Saw Vice</b></p> <p><b>Feature :</b> Made of cast iron, plain finished. Completed with toggle fastener.</p> <p><b>Specification :</b> Jaw width approx. : 150 mm Opening Jaw approx. : 130 mm Complete with fastener bolts and nuts.</p>	32 Pcs
30	<p><b>Saw Set</b></p> <p><b>Feature :</b> Pistol grip style with power full leverage handless back, panel, hand and Has calibrated anvil wheel with positive locking screw to set pitch Clear view allows accurate tooth. Unique magnifying lens over setting is for better visibility. Easy dial adjustment. centering.</p> <p><b>Specification :</b> Set any saw with 4 to 16 teeth per inch by simply squeezing handle.</p>	8 Unit
31	<p><b>Jointer Plane</b></p> <p><b>Feature :</b> Corrugated sole. Double irons, conveniently fastened by means of A cam-lever for line adjustment of depth of cut and lateral movement. Plastic handle and knob blue japanned finish.</p> <p><b>Specification :</b> Length. Approx. = 550 mm Cutter width = 60mm</p>	48 Unit
32	<p><b>Jack Plane</b></p> <p><b>Feature :</b> Corrugated sole. Double irons, conveniently fastened by means of a cam-lever locking device screw and lever for fine adjustment of depth of cut and lateral movement. Plastic handle knob blue japanned finish.</p> <p><b>Specification :</b> Length approx. = 355 mm Cutter width approx = 50 mm</p>	48 Unit
33	<p><b>Smooth Plane</b></p> <p><b>Feature :</b> Corrugated sole. Double iron, conveniently fastened by means of a cam-lever locking device screw and lever for fine adjustment of depth of cut and lateral movement. Plastic handle and knob blue japanned finish.</p> <p><b>Specification :</b></p>	24 Unit

NO.	NAME AND SPECIFICATION OF TOOLS AND EQUIPMENT	TOTAL QTY
34	<p>Length approx. = 240 mm Cutter width approx. = 50 mm</p> <p><b>Block Plane</b></p> <p><b>Feature :</b> With adjustable mouth and screw and lever for adjusting depth of cut and lateral movement. Sides have specially formed hand-holds-Black japanned and nickel-plated.</p> <p><b>Specification :</b> Overall length approx. = 160 mm Width of cutter approx. = 40 mm</p>	24 Unit
35	<p><b>Rebate Plane</b></p> <p><b>Feature :</b> Two cutter positions, one for normal and one for bull-nose work. Lever for easy adjustment of cutter. Fitted with spur and removable depth gauge and adjustable fence for use on either side. Completed with spare cutters.</p> <p><b>Specification :</b> Overall length = 215mm Width of cutter = 40mm</p>	8 Unit
36	<p><b>Curve Bottom Spokeshave</b></p> <p><b>Feature :</b> For plane an angle to surform a flat shapes.</p> <p><b>Specification :</b></p> <ul style="list-style-type: none"> <li>- Blade width approx. = 55 mm</li> <li>- Adjustable cutter</li> <li>- Grey iron blade</li> <li>- Designed in accordance with modern ergonomic principles</li> <li>- Round bottoms</li> </ul>	8 Unit
37	<p><b>Flat Spokeshave</b></p> <p><b>Feature :</b> Two screws for adjusting the cutter.</p> <p><b>Specification :</b></p> <ul style="list-style-type: none"> <li>- Blade width approx. = 55 mm</li> <li>- Adjustable cutter</li> <li>- Grey iron blade</li> <li>- Designed in accordance with modern ergonomic principles</li> <li>- Flat bottoms</li> </ul>	8 Unit
38	<p><b>Hatchet</b></p> <p><b>Feature :</b> Extra large, crowned milled face-Polished striking head and</p>	8 Pcs

NO.	NAME AND SPECIFICATION OF TOOLS AND EQUIPMENT	TOTAL QTY
39	bevel-Hickory handle <b>Specification :</b> Weight = approx. 15lbs Length = approx. 15" <b>Firmer Chisel</b>	24 Set
40	<b>Feature :</b> All purpose chisels for heavy work or fine cutting. Sharp, bevel edged blade. <b>Specification :</b> Set of 4 pieces. 1/4", 1/2", 3/4", 1" Supplied in case. <b>Mortise Chisel</b>	24 Set
41	<b>Feature :</b> All purpose chisels for heavy work or fine tipped hickory handles absorb mallet impact. One piece high carbon tool steel blade and socket for maximum durability. Sharp, bevel edged blade. <b>Specification :</b> Set of 8 pieces from 6 to 25 mm Supply in case. <b>Turning Chisels Set</b>	8 Set
42	<b>Feature :</b> In forged tool steel, high quality tool, used for wood turning lathe <b>Specification :</b> - Turning Chisel with woden handles, width : 6 mm, 12 mm, 20 mm, 24mm - Hollow Chisel woth wooden handle, width : 6 mm, 12 mm, 20 mm - Convex chisel woth wooden handle, width : 6 mm, 12 mm, 20 mm - Pointed Chisel woth wooden handle, width : 6 mm, 12 mm, 20 mm - Round Chisel woth wooden handle, width : 6 mm, 12 mm, 20 mm - Cutting of Chisel woth wooden handle, width : 6 mm, 12 mm Supply in case = 3 pcs Plastic tool Box <b>Specification :</b> - Made of PP plastic - Fully lockable for security of components - Ideal for movable activities - Top handle allow ways carrying - L: 600 mm, H: 35 mm, W: 35 mm (approx) <b>Carving Tools</b>	8 set
	<b>Feature :</b> Twelve professional quality tools for carrying patterns and designs in wood, linoleum and other soft materials. Hand forged from high quality tool steel, ground and tempered to hold a keen edge, sturdy wood handles.	

NO.	NAME AND SPECIFICATION OF TOOLS AND EQUIPMENT	TOTAL QTY
43	<p><b>Specification :</b> 12 pieces set of various chisels and gauges. Supplied in wooden box.</p> <p><b>Hand Drill</b></p> <p><b>Feature :</b> Machine cut gear teeth and double pinions. Parallel sided frame die cast of aluminum. Three jaw duck. Hollow wood handle for drill storage.</p> <p><b>Specification :</b> Chuck capacity = 1/4" Overall. Length = 12"</p>	8 unit
44	<p><b>Bit Brace</b></p> <p><b>Feature :</b> Bit brace with fully boxed ratchet-self centering chuck holds round or square bit from 1/8 to 1/2" in diameter. Ball bearing head and sweep. Zinc plated chromate finish with wood handle and head.</p> <p><b>Specification :</b> Chuck size approx: 13" Length approx. = 12"</p>	8 unit
45	<p><b>Long Handle Auger Bit</b></p> <p><b>Feature :</b> A general purpose bit for boring in practically every kind of wood-Made of steel with a polished finish. Heat treated and tempered full length. Bit has double spurs, double cutters and medium fast screw pitch. Open throat design clears chips quickly to prevent clogging and binding.</p> <p><b>Specification :</b> Set of 8 pieces. Size : 6 to 20 mm, Length approx. 460 mm Supplied in case</p>	4 Set
46	<p><b>Auger Bit</b></p> <p><b>Feature :</b> A general purpose bit for boring in practically every kind of wood - Made of steel with a polished finish. Heat treated and tempered full length. Bit has double spurs, double cutters and medium fast screw pitch. Open throat design clears chips quickly to prevent clogging and binding. Supplied in a hardwood case with bits secured by spring clips and sizes marked on liner.</p> <p><b>Specification :</b> Set of 6 pieces, length approx. 230mm From 6 to 20 mm Supplied in case</p>	4 Set
47	<p><b>Expansive Bit</b></p>	8 Pcs

NO.	NAME AND SPECIFICATION OF TOOLS AND EQUIPMENT	TOTAL QTY
48	<p><b>Feature :</b> For boring holes beyond the size range of regular brace bits. Drop forged, fully polished. Wedge type blade lock holds cutter in place one it is set for desired hole size. Open - throat design clear chips rapidly.</p> <p><b>Specification :</b> Bit for hole die range = 7/8" to 3"</p>	8 Set
49	<p><b>Feature :</b> Use for make a holes with different size</p> <p><b>Specification :</b> - High Speed Steel - 25 pcs from 1mm to 13mm</p> <p>- Supply in steel box</p>	8 Pcs
50	<p><b>Feature :</b> A high speed steel countersink for use where drilled holes are to small for a multiple flute tool to enter. Also for applications in which multiple flute tools chatter.</p> <p><b>Specification :</b> Five flutes, square shank, 90° set of 5 pieces. Size = 1/4" to 3/4"</p>	8 Pcs
51	<p><b>Feature :</b> For general wood boring with 1/4" power drills and drill presses. Ideal for drilling straight or angled holes in hard and shaft wood in cladding plywood. Bit is forged from steel and heat treated full length. Has a hollow ground point and hexagon shank.</p> <p><b>Specification :</b> Set of 13 pieces. One each of 1/4, 5/16, 3/8, 7 1/16, 1/2, 9/16, 5/8, 11/16, 3/4, 7/8, 15/16 and 1" diameter size. Supply in Case</p>	8 Pcs
51	<p><b>Feature :</b> Ideal for drilling straight holes in hard and soft wood. With twisted ring handle hollow is bright polished.</p> <p><b>Specification :</b> Set of 3 pieces. One each of = 2, 4, and 6mm, diameter size length = 160mm</p>	8 Pcs

NO.	NAME AND SPECIFICATION OF TOOLS AND EQUIPMENT	TOTAL QTY
52	<p><b>Claw Hammer</b></p> <p><b>Feature :</b> General purpose hammers have hickory handle securely wedged into the heads curve type, with smooth striking face.</p> <p><b>Specification :</b> High quality Weight = 16 oz Handle length = 12½"</p>	24 Pcs
53	<p><b>Ball Pein Hammer</b></p> <p><b>Feature :</b> hammer is forged from high carbon steel. Black finished head with polished faces are securely wedged into hickory handle.</p> <p><b>Specification :</b> Weight = 24 oz Overall length = 15 ½"</p>	24 Pcs
54	<p><b>Magnetic Tack Hammer</b></p> <p><b>Feature :</b> Also called upholstery hammer forged tool steel. Small circular face for driving tacks in confined areas. One end of head magnetized for holding tacks. Hickory handle.</p> <p><b>Specification :</b> Weight = 5 oz Overall length = 11½"</p>	24 Pcs
55	<p><b>Nail Set/Punch</b></p> <p><b>Feature :</b> Made of one piece alloy steel, tempered for durability. Polished head and point.</p> <p><b>Specification :</b> Set of 3 pieces. One each of 1.6, 2.3, 3.2 mm, length 100mm.</p>	8 Set
56	<p><b>Center Punch</b></p> <p><b>Feature :</b> High grade forged round. Knurled steel. Polished head and points. Black lacquer finished.</p> <p><b>Specification :</b></p>	8 Set

NO.	NAME AND SPECIFICATION OF TOOLS AND EQUIPMENT	TOTAL QTY
57	<p>Set of 4 pieces.</p> <p><b>Screwdriver Set with Case</b></p> <p><b>Feature :</b>            Bor. on steel blades are forged and heat treated for high strength and heavy duty use. Have full size deep fluted plastic handles.</p> <p><b>Specification :</b>            12 pcs set of slot type and Philips type.</p> <p>slotted size: 9.5x20 Hex 16, 8x150 Hex 14, 6x100 Hex 13, 5x75 Hex 11, 6x38 Hex13, 3x75</p> <p>Philips size: 3/8"x8" #4 Hex 5/8" (#4x200 Hex 15), 5/16"x6" # 3 Hex 9/16", 1/4"x4" #2 Hex 1/2", 3/16"x3" #1 Hex 7/16", 1/4"x1 1/2" #2 Hex 1/2", 1/8"x3" #0</p> <p>Plastic (PP) case</p>	8 Set
58	<p><b>Swivel Ratchet Screwdriver</b></p> <p><b>Feature :</b>            High torque ratchet with swivel head.</p> <p><b>Specification :</b>            15 pieces /set            Bits stored in 2 round plastic boxes.</p>	8 Unit
59	<p><b>Wood Rasp</b></p> <p><b>Feature :</b>            Cabinet rasp. For use by cabinet makers and wood workers. With half round cross section.</p> <p><b>Specification :</b>            Length = 200mm</p>	24 Pcs
60	<p><b>Round Rasp</b></p> <p><b>Feature :</b>            For use by cabinet makers and wood workers. With round cress section</p> <p><b>Specification :</b>            Round tapering to wards the end            Length = 200mm</p>	24 Pcs
61	<p><b>File</b></p> <p><b>Feature :</b>            Regular taper saw files. For 60° saw teeth. Single cut; set &amp; cut edges for gullets, 6" x 29/32" x 17/16"            Supply in case</p>	24 Set
62	<p><b>Oilstone</b></p>	48 Pcs

NO.	NAME AND SPECIFICATION OF TOOLS AND EQUIPMENT	TOTAL QTY
63	<p><b>Feature :</b> Combination oilstones. Oil filled aluminum oxide India bench stones are coarse grit on one side, fine grit on one side, fine grit on other side.</p> <p><b>Specification :</b> Shape = Rectangular Size = 8" x 2" x 1"</p> <p><b>Slipstone</b></p>	48 Pcs
64	<p><b>Feature :</b> Especially designed for lapping inside or outside curve surfaces, sharpening gouges and curved cutting edges. Fine grit aluminum Oxide.</p> <p><b>Specification :</b> Size = 6" x 2" x 5/8"</p> <p><b>Putty Knives</b></p>	48 Pcs
65	<p><b>Feature :</b> Heavy gauge tool steel blade, hardened and tempered. Mirror finish blade runs through entire handle. Hardwood handle held with brass rivet. Flexible blade.</p> <p><b>Specification :</b> Blade size = 2" x 3 1/2" Overall length = 7 1/4"</p> <p><b>Plastic Mallet</b></p>	48 Pcs
66	<p><b>Feature :</b> Use where a metal hammer would damage the work.</p> <p><b>Specification :</b> Weight = 8 oz Head size = 1 3/4" x 3 1/4"</p> <p><b>Pliers</b></p>	48 Pcs
67	<p><b>Feature :</b> Strong and durable to meet the heavy duty requirements of linemen and electricians hardened and heat treated, with finely honed polished cutting heads that cut many gauges of wire. Cushion grip.</p> <p><b>Specification :</b> 3 pieces/ set Size = 6"</p> <p><b>Pincer</b></p>	24 Pcs

NO.	NAME AND SPECIFICATION OF TOOLS AND EQUIPMENT	TOTAL QTY
68	<p><b>Feature :</b> For use by carpenters, concrete form builders to cut wire, nails and spikes. Drop forged with hand field cutting edges. Polished head enamel handles.</p> <p><b>Specification :</b> Nominal length = 10"</p> <p><b>Metre Box Clamp</b></p>	8 Unit
69	<p><b>Feature :</b> Acts as a corner clamp to hold wood for gluing or nailing. Meter box clamps wood firmly while sawing-saw travels smoothly in special channel. Made aluminium, alloy. Screw holes for fastening to work bench.</p> <p><b>Specification :</b> - Quick acting corner clamp 65 x 70mm (Approx.)</p> <p><b>T Bar Clamp</b></p> <p><b>Feature :</b> For hold and clamp one or more part of object in large size Easy to adjusted of the jaw Has a screw part and handle to clamp High carbon steel</p> <p><b>Specification :</b> Set of the following size - Jaw opening approx. 1000mm - Jaw opening approx. 1500mm - Jaw opening approx. 2500mm - One set = 3 pcs of bar clamp in the same size.</p>	24 Unit
70	<p><b>Radial Arm Saw *)</b></p> <p><b>Feature :</b> Industrial radial arm saw for across cut, rip, bevel rip, meter, bevel meter, dado and plough cutting. Retractable glide arm travels full stroke on sealed ball bearings. Moves out of the way at a touch. Rugged steel casting construction throughout. Low voltage magnetic starter convenient adjustment and locking controls. Clear view of work area.</p> <p><b>Specification :</b> * Three phase motor : 4HP, 380V, 50Hz * Motor speed : 3000rpm  * Blade Ø : 355mm or 305mm  * Cross cut capacity : 680mm * Cross cut capacity at 45° : 453mm  * Rip capacity : 860mm * Meter locating stops : -45° / 0° / +45° * Bevel locating stops : 0° / 45° / 90°</p>	4 Unit

NO.	NAME AND SPECIFICATION OF TOOLS AND EQUIPMENT	TOTAL QTY
71	<p><b>Tilt Arbor Saw *)</b></p> <p>* Spindel Ø : 25.4mm  * Bearing of roller head : 4  * Table size : 889 x 787mm  Complete with blade o 355 mm or 305 mm TCT  Complete with operation manual in English and Bahasa Indonesia</p> <p><b>Feature :</b>  Rise the fall tilt arbor circular saw benches fitted with 300 mm diameter tungsten carbide tipped saw blade as standard equipment. The all stell table is accurately machined and mounted on 8 mm thick steel body.</p> <p><b>Specification :</b>  * Height of cut standard : 0 - 75mm  Max : 100mm  * Width of cut standard : 0 - 430mm  Max : 1,250mm  * Saw blade dia. Standard : 300mm  * Saw blade bore : 0 - 45°  * Angle adjustment distance  * Saw blade center to front table : 390mm  * Max. cross cut length : 1,250mm  * Table size : 1,020 x 760mm  * Table height : 880mm  * Motor power : 2 HP  * Motor Speed : 4,000rpm  * Shipping size : 0.9 m³  * Completed with blade and spare. Saw blade dia standard : 300mm, TCT  Complete with operation manual in English and Bahasa Indonesia</p>	4 Unit
72	<p><b>Band Saw *)</b></p> <p><b>Feature :</b>  Rigid 14 gauge, are welded steel construction, elastomer motor mounts for minimal noise and vibration, upper and lower wheel that rotate on double sealed permanently lubricated ball bearing bad roller bearing blade guides controlled by a simple cam adjustment work table tells 45° right, 10° left. Transparent plastic blade guards protect all the way surface. Guard swings away to allow fast blade changes through slot at the front of machine.</p> <p><b>Specification :</b>  * wheel diameter : 500mm  * R.P.M of wheels : 720rpm  * Max. height of cut : 300mm  * Max. cut width : 475mm  * Max. saw length : 3,999mm  * Size of table : 680 x 520mm  * Motor power : 2HP  * Shipping size : 1,970 x 580 x 1,010mm  Complete with saw blade ½" and 1" = 2 set  Complete with operation manual in English and Bahasa Indonesia</p>	4 Unit
73	<p><b>Jointer Planer *)</b></p>	4 Unit

NO.	NAME AND SPECIFICATION OF TOOLS AND EQUIPMENT	TOTAL QTY
74	<p><b>Thickening Planer *)</b></p> <p><b>Feature :</b></p> <ul style="list-style-type: none"> <li>* Accurate parallelogram design enables table to travel in the same arc as the cutting circle, maintaining close and uniform clearance between table lip and cutterhead for safest operation regardless of cutting depth.</li> <li>* Front Cutterhead Guard, gives maximum protection to the operator.</li> <li>* Noise Reduction Tabel Lips.</li> <li>* Large Stable Quick-set Fence.</li> <li>* Center-mounted fence</li> <li>* Rabbeting Ledge. Maximum rabbeting depth : 3/4"</li> <li>* Motor standard metric totally enclosed fan cooled.</li> </ul> <p><b>Specification :</b></p> <p>Cutting width capacity : 304.8mm (12")</p> <p>Cutting depth capacity : 19mm (3/4")</p> <p>Table size - Width : 304.8mm (12") - Length : 2,133mm (84")  height from floor : 800mm (31 1/2")</p> <p>Fence : - Size (LxH) : 1194 x 140 mm (47x5 1/2")  Tilt degree : 45° (F &amp; R)  Positive stops : 40°, 90°, 135°</p> <p>Cutterhead:</p> <ul style="list-style-type: none"> <li>- Speed : 5000rpm</li> <li>- Number of knives : 3</li> <li>- diameter : 100mm (3 15/16")</li> <li>- cutting circle : 104mm (4 3/32")</li> <li>- Rabbeting capacity : 19mm (3/4")</li> </ul> <p>Dimension : 2165 x 910 x 940mm  Motor power 380V, 3 phase : 3HP  Completed with TCT blade  Complete with operation manual in English and Bahasa Indonesia</p>	4 Unit
	<p><b>Feature :</b></p> <ul style="list-style-type: none"> <li>* Main framework, constructed from pressed steel, using numerical control machines which work to thousands of an in tolerances.</li> <li>* Table raise and lowered by a lead - screw turning within a ground cylindrical past packed with grease. 4 right angle guides offering 8 contact - faces guarantee maximum stability and perfect parallel between tool and table.</li> <li>* Feed through rollers, 3 large - diameter rollers feed work pieces through the machine. All are driven and suspended from sealed bearings which require no lubrication. Whatever. The rollers are provided with a special slip-arrangement which ensures constant and even pressure on the work piece, essential if vibration is to be avoided when handling this work. Feed through, infinitely variable feed. Drive by 1HP motor. Feed reduction unit runs in oil. Motors, 3 independent motors drive the spindle, work the feedthrough rollers, and raise/lower the work table.</li> </ul> <p><b>Specification :</b></p> <ul style="list-style-type: none"> <li>* Max. planing width : 630mm</li> <li>* Max. planing tickness : 300mm</li> <li>* Max. depth of cut : 8mm</li> <li>* Min. length of workplence : 220mm</li> </ul>	

NO.	NAME AND SPECIFICATION OF TOOLS AND EQUIPMENT	TOTAL QTY
75	<p><b>Wood Turning Lathe *)</b></p> <ul style="list-style-type: none"> <li>* Cutter block speed : 4,800rpm</li> <li>* Number of knives : 4 pcs, TCT</li> <li>* Dia. of four knives cutter block : 98mm</li> <li>* Cutting circle : 102mm</li> <li>* Table Size (W x L) : 685mm x 870mm</li> <li>* In-feed rollers : 76mm</li> <li>* Out feed (solid) : 60mm-two</li> <li>* Table roll (Solid) : 72mm-two</li> <li>* Spindle motor 380V, 3 phase, 7.5HP</li> <li>* Feeding motor 380V, 1 phase, 1/2HP</li> <li>* Table adjustment motor 380 Vm, 3 phase, 1/2HP</li> <li>* Overall dimensions 1,305 x 960 x 1,200mm</li> </ul> <p>Complete with operation manual in English and Bahasa Indonesia</p> <p><b>Feature :</b></p> <ul style="list-style-type: none"> <li>* (The machine can turn wood pieces having a max. diameter of 500 mm.) Further more it offers the possibility to use various driving centers, to fit ball bearings centers and at last, the possibility to fit on the rear face plate wood pieces of large diameter.</li> <li>* A set of optional accessories make this machine particularly versatile and readily suitable for any manual working.</li> </ul> <p><b>Specification :</b></p> <ul style="list-style-type: none"> <li>* Working length : 1,000mm</li> <li>* Center height : 210mm</li> <li>* Motor 380V, 3 phase : 0.75kW</li> <li>* Spindle speeds</li> <li>* variable : 400 - 3,400rpm</li> <li>* 6 speeds</li> <li>* Max. working draw : 500mm</li> <li>* Overall dimension with stand approx. <ul style="list-style-type: none"> <li>- Length : 2,670mm</li> <li>- Width : 400mm</li> <li>- Height : 1,222mm</li> </ul> </li> <li>* Shipping size : 1.8m<sup>3</sup></li> </ul> <p>Complete with operation manual in English and Bahasa Indonesia</p>	4 Unit
76	<p><b>Bench Drilling Machine *)</b></p> <p><b>Feature :</b></p> <p>Modern design, stable construction ground steel spindles mounted on precision bearing.  Machine base plate, machine length.  Drill depth adjustment.  Drilling spindle runs in precision ball bearing and is guided in a hollow shaft with spline - bore hubs. The drive belt can be shifted easily by means of a lever which disengages the motor and relieves the belt tension. Manual feed in machine light.</p> <p><b>Specification :</b></p> <ul style="list-style-type: none"> <li>* Drilling capacity : 5 - 25mm</li> <li>* Chuck capacity : 20mm</li> <li>* Collar diameter : 75mm</li> <li>* Taper of spindle : MT3</li> <li>* Swing : 432mm</li> <li>* Spindle travel : 80 mm</li> <li>* Number of speed : 4</li> </ul>	4 Unit

NO.	NAME AND SPECIFICATION OF TOOLS AND EQUIPMENT	TOTAL QTY
77	<p><b>Bench Grinder</b></p> <p>* Rpm of spindle : 160 - 3000rpm  * Column diameter : 80mm  * Table size : 356 x 356mm  * Base size : 498 x 350mm  * Total height : 1,635mm  * Motor : 1 HP  * Dimension : 1,410 x 540 x 265mm  * Include heavy duty vices make a cast iron;  - jaw opening approx. 140mm  - jaw width approx.150mm  Complete with operation manual in English and Bahasa Indonesia</p> <p><b>Feature :</b>  Easily mounted on work bench and connected to motor for all types of grinding operations. Double shielded ball bearings are lubricated for life. Rigid iron construction. Equipped with heavy duty adjustable guard and tool Rests. Furnished with to vitrified aluminum oxide wheels in medium and coarse grits.</p> <p><b>Specification :</b>  * Wheel size : 8" x 1" x 58"  * Shaft Ø : 5/8"  * Motor 220V, 1 Phase : 1/2HP  Complete with operation manual in English and Bahasa Indonesia</p>	8 Unit
78	<p><b>Belt &amp; Disc Sander</b></p> <p><b>Feature :</b>  Excellent for metals, wood and plastics. For smoothing, facing, beveling, metering, chamfering and forming curve. Complete with tilting belt arm, tilting disc table, 1.75 + 2.5HP motor, sanding disc Ø 350mm sanding belt 1,716 x 150mm, and stand.</p> <p><b>Specification : (approx.)</b>  Width of belt : 152.4mm (6")  Length of belt : 1,524mm (60")  Fence tilt : 45°  RPM : 1,400 / 2,800 rpm  Diameter of sanding disc : 355.6 mm (14")  Motor 220V, 1 phase : 1 HP.  Tilt of sanding table : 90°  Overall dimensions : 970 x 780 x 830mm  Shipping size : 1m<sup>3</sup>  Complete with operation manual in English and Bahasa Indonesia</p>	4 Unit
79	<p><b>Circular Saw Setter *)</b></p> <p><b>Feature :</b>  Hand operated for setting combination, rip or cross cut circular saw. Mount of bench. Quadrant allows alignment of hammer with tooth center for positive uniform set. Safety key.</p>	4 Unit

NO.	NAME AND SPECIFICATION OF TOOLS AND EQUIPMENT	TOTAL QTY
80	<p>Variable angle adjustment.</p> <p><b>Specification :</b></p> <p>Depth of cross cut at 90° : 85mm            Depth of cross cut at 45° : 80mm            Power required : 220 - 240V / 1700W            Saw blade diameter : 230mm            Speed (without load) : 4000 rpm</p> <p>Complete with operation manual in English and Bahasa Indonesia</p> <p><b>Portable Circular Saw *)</b></p> <p><b>Feature :</b></p> <ul style="list-style-type: none"> <li>* All round guideplate, both side can be used to follow fences clamped on the work.</li> <li>* Blade guard with saw dust outlet at the extreme end for good control of the saw dust.</li> <li>* The saw cut can see clearly.</li> <li>* Ideal cut indicator, shows exactly where to cut, even with bevel cut.</li> <li>* Ideal cut indicator, shows exactly where to cut, even with bevel cut.</li> <li>* If the saw dust is to be sucked out with the vacuum cleaner, the appropriate extraction nozzle can be fitted to the saw dust outlet of the tool.</li> </ul> <p><b>Specification :</b></p> <ul style="list-style-type: none"> <li>* Depth of cut adjustable : 0 - 62mm</li> <li>* Saw blade diameter : 184mm</li> <li>* Power input : 1,400 watts</li> <li>* No-load speed : 4,800 rpm</li> <li>* Saw blade tills for beveled cut : 0 - 45°</li> </ul> <p>Complete with operation manual in English and Bahasa Indonesia</p>	4 Unit
81	<p><b>Portable Jig Saw *)</b></p> <p><b>Feature :</b></p> <ul style="list-style-type: none"> <li>** Ideal sawing or trimming boards, panels, beams, battens etc. The setting of saw angles is as sample as can be. Has double insulation and are radio and T.V suppressed. An enormous selection of jig saw blades are available, offering the right blade for every job and material.</li> <li>* electronic speed control with pre-selector</li> <li>* Base plate can move or swivels to sides way and can draw to back way.</li> </ul> <p><b>Specification :</b></p> <p>Switch : Vari Tronic            Depth of cut Wood : 60mm            Depth of cut Aluminum : 6mm            Depth of cut Steel : 3mm            Speed without load : 500 - 3200rpm            Power required : 420 watts</p> <p>Complete with operation manual in English and Bahasa Indonesia</p>	8 Unit

NO.	NAME AND SPECIFICATION OF TOOLS AND EQUIPMENT	TOTAL QTY
82	<p><b>Portable Planer *)</b></p> <p><b>Feature :</b>  All carbide cutter blades, even suitable for edging chip board and for planing and grain. Vee groove in front part of planer sole and tillable planing guide for easy chamfering with reversible all carbide cutter blades.  Cutter blades protected in stop position.</p> <p><b>Specification :</b></p> <p>Planing width : 82mm  Planing depth adjustable : 0.5 to 1.5 mm  Max. Rating depth : 0 - 8mm  Power input : 500 watts  No-load speed : 19,000 r.p.m  Supplied with planing guide and rebating depth stop.  Complete with operation manual in English and Bahasa Indonesia</p>	8 Unit
83	<p><b>Portable Electric Drill *)</b></p> <p><b>Feature :</b>  Robust motors and heavy duty gears for hard continuous applications.  Safety coupling  Electronic controller for accurate and sensitive drilling.</p> <p><b>Specification ;</b></p> <p>Capacity in steel : 10mm  Capacity in concrete : 20mm  Capacity in wood : 30mm  Power input : 500 watts, 220V  No-load speed : 0 - 3,900rpm  Weight approx : 2.3 kg  Supplied with geared chuck.</p>	8 Unit
84	<p><b>Portable Router *)</b></p> <p><b>Feature :</b>  Circular base plate, the router cutter always operates at the same distance from the edge of the work.</p> <p><b>Specification :</b></p> <ul style="list-style-type: none"> <li>- For make an angle/shape edge</li> <li>- Double insulation 220V, approx. 900W/50Hz</li> <li>- Cutter speed approx. 25000 RPM</li> <li>- Collate dia. approx. 6mm, 12mm</li> <li>- Power supply cord 5m complete with accessories</li> <li>- Trimmer guide 1 pc</li> <li>- Straight guide 1 pc</li> <li>- Template guide 1 pc</li> <li>- Collate sleeve 1/4 ; 1 pc</li> <li>- Wrenches 1 pc</li> <li>- Straight bit (carbide tipped); 1 pc</li> <li>- Steel carrying case</li> <li>- Operating and maintenance manual books and straight bits (1/4" shank) 4 pcs</li> <li>- Corner rounding bits (1/4" shank) 2 pcs</li> </ul>	8 Unit

NO.	NAME AND SPECIFICATION OF TOOLS AND EQUIPMENT	TOTAL QTY
	<p>Ball bearing bending champering bits (1/4" shank) 1 pc  - Cutting dia. Approx. 1 1/8"  - TCT type  Ball bearing bending bits (1/4" shank) 1 pc  - Cutting dia. Approx. 1 1/8"  - TCT type  Ball bearing roman degree bits (1/4" shank) 1 pc  - Cutting dia. Approx. 1 1/8"  - TCT type  Ball bearing cove bending bits (1/4" shank) 1 pc  - Cutting dia. Approx. 1 1/8"  - TCT type  Dovetail TCT bits (1/4" shank) 1 pc  - Cutting dia. Approx. 1 1/8"  - TCT type  Dovetail bits (1/4" shank) 1 pc  - Cutting dia. Approx. 1 1/8"</p> <p>All bits supply in Case made of PP plastics or wooden good quality</p>	
85	<p><b>Portable Belt Sander</b></p> <p><b>Feature :</b>  The belt sander if fitted with the unique skill Automatic Belt Control (ABC) system. This system automatically aligns the belt while you are working, thus eliminating any tiresome adjustments, even after changing belts itself a simple tasks. The skill belt sander is double insulated and radio/t.v suppressed. A complete range of belts suited to every job and type of materials is available.  The addition handle can be removed to sanding the corner of object.</p> <p><b>Specification :</b>  Belt size : 75 x 533mm  Sanding surface : 75 x 130mm  Belt speed r.p.m - No. load : 200 - 300rpm  Power Input : 710 watts, 220V  Weight approx. : 3.2kg  Complete with instruction manual in English and Bahasa Indonesia</p>	4 Unit
86	<p><b>Hack Saw</b></p> <p><b>Feature :</b>  Plated tubular baw frame has oval cross section for excellent rigidity and balance. Allows clear, unobstructed view of work area sturdy, die cast guarded grip handle die cost pressure for maximum efficiency.  Extra blades store in tube.</p> <p><b>Specification :</b>  Throat depth : 4"  Furnished with 12", 24 TPI blade adjusts to hold 10" blade.</p>	48 Pcs
87	<p><b>Spray Gun Unit</b></p> <p><b>Feature:</b>  Spray gun with fluid cup provided with rapid hook closing</p> <p><b>Specification :</b>  - Tank capacity :1000 cm3</p>	4 Pcs

NO.	NAME AND SPECIFICATION OF TOOLS AND EQUIPMENT	TOTAL QTY
88	<p>- Max. Operating pressure: 4 to 8 bars  - Air consumption : 100 to 200 l/min  - Hose (dia. Fit to spray gun nipple) Length : 10m</p> <p><b>Glass Cutter</b></p> <p><b>Feature :</b>  High quality industrial diamond produces a clear, deep score in the glass to assure a perfect break. Has swivel head, break rack and rosewood handle with ball end.</p> <p><b>Specification :</b>  Length : 7 1/8"</p>	8 Pcs
89	<p><b>Oil Can</b></p> <p><b>Feature :</b>  Versatile oiler for ASE in the workshop-Positive acting hydraulic pump with machined plunger and steel ball valve is removable for easy cleaning and replacement.  Spout is detachable. Full drawn, seamless steel body has leak proof bottom.</p> <p><b>Specification :</b>  Capacity : 100 ounce  Spout position : 50° angle  Spout length : 6" flexible</p>	24 Unit
90	<p><b>Goggle</b></p> <p><b>Feature :</b>  Safety goggle for general use. All plastic, indirect ventilation Eye protection against common working hazards.</p> <p><b>Specification :</b>  Clear frame  Clear acetate lens</p>	96 Pair
91	<p><b>Adjustable Wrenches</b></p> <p><b>Feature :</b>  Made of forged alloy steel, chrome plated. Chusion grip provided by transparent green vinyl bonded to handle. Gripes resistance to grease and will not crack or chip.</p>	48 Pcs

NO.	NAME AND SPECIFICATION OF TOOLS AND EQUIPMENT	TOTAL QTY
92	<p><b>Specification :</b> Length approx.: 12" Capacity : 1 5/16"</p> <p><b>Double Open end Wrenches</b></p> <p><b>Feature :</b> Alloy steel wrenches are drop forged and assure ample strength for the severest uses. Finish is chrome plated.</p>	24 Set
93	<p><b>Specification :</b> Long pattern Set of 11 pieces. One each of :6x7; 8x9; 10x11; 12x13; 14x15; 16x17; 18x19; 20x22; 21x23; 24x27 and 25x28 mm</p> <p><b>Box Wrenches</b></p> <p><b>Feature :</b> For service woodworking machine</p> <p><b>Specification :</b></p> <ul style="list-style-type: none"> <li>- 11 pcs sockets 1/4" DR., 6 point (inches)</li> <li>- 11 pcs sockets 1/4" DR., 6 point (mm)</li> <li>- 10 pcs deep sockets 1/4" DR, 6 point (inches)</li> <li>- 11 pcs deep sockets 1/4" DR, 6 point (mm)</li> <li>- 1 pc quick release ratchet (screw type)</li> <li>- 1 pc 3" extension Bar</li> <li>9 pcs sockets 3/8" DR, 6 point (inches)</li> <li>14 pcs socket 3/8" DR, 6 point (mm)</li> <li>9 pcs deep socket 3/8" DR, 6 point (inches)</li> <li>11 pcs deep socket 3/8" DR, 6 point (mm)</li> <li>1 pc quick release ratchet (screw type)</li> <li>1 pc 3" extension bar</li> <li>2 pcs 5/8" + 13/16 spark plug socket</li> <li>20 pcs socket 1/2" DR, 6 point</li> <li>1 pc 1/2" quick release ratchet (screw type)</li> <li>12 pcs combination wrenches</li> <li>11 pcs hex key</li> <li>10 pcs bits</li> <li>1 pc reversible ratcheting driver</li> </ul>	4 Set
94	<p><b>Brush</b></p> <p><b>Feature :</b> Used on finer; smoother surface such as doors and cabinets. White tampico fiber bristles with metal ferrule, wood handle.</p>	96 Pcs

NO.	NAME AND SPECIFICATION OF TOOLS AND EQUIPMENT	TOTAL QTY
95	<p><b>Specification :</b> Width : 1" Length : 5"</p> <p><b>Scissors</b></p> <p><b>Feature :</b> Good quality shears are ideal for most cutting jobs on any materials. Hot drop forged from a single piece of high carbon steel. Blades are hardened, ground and adjusted for true cutting.</p> <p><b>Specification :</b> Beat handle knives edge solid steel shears Overall length : 10" Length of cut : 4 7/8" Blade finish : nickel plate</p>	24 Pcs
96	<p><b>Cable/Cord Reel</b></p> <p><b>Feature :</b> 75 Ft. cable reel with two outlet. Plug into a wall outlet and carry up to 75 ft away. Made of tough ABS plastic. Complete with cable/cord</p> <p><b>Specification :</b> Cord size : Ø 3/8" Length of cord approx. : 75ft</p>	4 Unit
97	<p><b>"F" Clamp</b></p> <p><b>Feature :</b> Forged frames are made in pattern process of high strength head treated steel. Have full length screws which are treated to resist bending and thread damaged.</p> <p><b>Specification:</b> 3 pc set Set of the following size approx : Jaw open : 150 mm Jaw open : 200 mm Jaw open : 300 mm Jaw open : 400 mm Jaw open : 500 mm One set = 2 pcs of F clamp in the same size.</p>	24 Set
98	<p><b>Scroll Saw</b></p> <p><b>Feature :</b> The scroll saw is used for wood variety cutting, made of cast iron material. Mounted with a centrifugal brake motor for instan blade breaking</p> <p><b>Specification :</b> The specification approx : Motor : 240V/50Hz, 1/2 HP Speed : 1500</p>	4 Set

NO.	NAME AND SPECIFICATION OF TOOLS AND EQUIPMENT	TOTAL QTY
	Table tilts : 35" Table area : 485 x 500mm Maximum cutting capacity : 100 mm Blade length : 310mm Completed with : Standard accessories * 10 pcs of spare blades * Instruction manual	
99	<b>Dust Collector / Dust Extractor *)</b>  <b>Feature :</b> The dust collector/dust extractor is used for to such the dust recidue. Centrifugal-sepatator for excellent air polution control. Made of steel fan standard and alluminium motor frame. Handle for easy moving. <b>Specification :</b> The specification approx : Motor : 2 HP / 1500 Watt Air flow rate :33.4m3 / minute Hose diameter : 1000 mm Hose Length : 500 cm Filter area : 0.8 square meter Bag : Single bag: dia. 60cm; L: 150cm. Completed with : Bag. Cord cable. Hose, 10 pcs of spate bags, standard accessories and instruction manual.	4 set
100	<b>Air Compressor *)</b>  <b>Specification :</b> The specification approx : Specification: (Pressure Switch Type)  Pressure : 9kg/cm2  Power supply : 220V, 50Hz, 1 phase, 1HP  Air volume approx. : 85 liters  Instruction manual in English / Indonesia Additional equipment : 1 pc Spare "V" belts drive * Spray Gun nozele * Air regulator with water filter * Safety guard * 10 m, dia. 12 mm of airhose * 2 pcs air gun * 6 set nipple connector * Special attachment	4 Set
101	<b>Horizontal Drilling Machine *)</b>  <b>Features:</b> - Pneumatic foot pedal controls clamping and boring action	4 Unit

NO.	NAME AND SPECIFICATION OF TOOLS AND EQUIPMENT	TOTAL QTY
	<p>sequentially.</p> <ul style="list-style-type: none"> <li>- Simple air flow control valve adjusts rate of head travel.</li> <li>- Heavy cast iron table adjust up and down for varying stock thickness.</li> </ul> <p><b>Specification :</b>  Power Supply : 220V  Spindle Speed : 2860 rpm (50Hz), 3450 rpm (60Hz)  Spinder thread : M8 x1.25P(or 5/16" x 18UNC) / M10 x 1.5P  (or 7/16" x 14 UNC)  Boring stroke : 100 mm  Table size : 400 x 250 (mm)  Completed With :  <ul style="list-style-type: none"> <li>Standard accessories</li> <li>Depthstop bars.</li> <li>Instruction manual</li> </ul> Superior Quality</p>	
102	<p><b>First Aid Kit</b></p> <p><b>Specification :</b></p> <ul style="list-style-type: none"> <li>- The first Aid Guidance Card (1 unit)</li> <li>- Assortment of Sterile water proof plasters (40 approx)</li> <li>- Eye pad and bandage sterile (8 approx)</li> <li>- Triangular bandage (8 approx)</li> <li>- Assortment of safety pins (12 approx)</li> <li>- Medium sterile wound dressing (12 approx)</li> <li>- Large sterile wound dressing (8 approx)</li> <li>- Extra-Large sterile wound dressing (8 approx)</li> <li>- One bottle of Betadine</li> <li>- One bottle of Aspirine</li> </ul>	8 Set
103	<p><b>Fire Extinguisher</b></p> <p><b>Features :</b>  Dry chemical fire extinguisher, and applicable to wood, paper, textile, rubber, oil, gas and electric fires. Suitable for Class A, B, and C fires. To use a dry chemical powder and propellant should be CFC free. To come complete with mounting bracket.</p> <p><b>Specification :</b></p> <ul style="list-style-type: none"> <li>- Gross weight : approx. 5 kg</li> <li>- weight of agent : 2.0 kg approximately</li> <li>- Shooting range : 3 - 6 m</li> </ul>	8 Pcs
104	<p><b>Hearing Protection</b></p> <p><b>Features:</b>  For hearing protection in workshop. Protector comftrline medium/high performance ear muffs.</p> <p><b>Specifications:</b></p> <ul style="list-style-type: none"> <li>- Comfortline earmuffs : 25dB</li> <li>- Standard mark licensed to ANSI S3.19</li> </ul>	16 Pcs
105	<p><b>Saw Files</b></p>	24 set

NO.	NAME AND SPECIFICATION OF TOOLS AND EQUIPMENT	TOTAL QTY
106	<p><b>Cordless Drill *)</b></p> <p><b>Features:</b> Three-square, top grade, single cut, good quality, for sharpening saw teeth.</p> <p><b>Specifications:</b></p> <ul style="list-style-type: none"> <li>- Length approx. 100mm and 150mm</li> <li>- Include handle</li> </ul> <p><b>Features:</b> Drill / screw driver with universal fast charger</p> <p><b>Specifications:</b></p> <ul style="list-style-type: none"> <li>- Battery voltage : 7.2V</li> <li>- Speed Max. approx. 600 RPM</li> <li>- Screw dia. To 6mm</li> <li>- Capacity in wood dia. Approx 12mm</li> <li>- Include battery pack, wire loop, box and other accessories.</li> </ul>	8 Unit